

polyEpoxy resin impregnated glass fabric laminate board - has  
intermediate layer contg. acicular inorganic filler, useful for printed  
circuit boards

Patent Assignee: HITACHI CHEM CO LTD (HITB )

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 1222950	A	19890906	JP 8850484	A	19880303	198942 B

Priority Applications (No Type Date): JP 8850484 A 19880303

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
JP 1222950	A	3		

Abstract (Basic): JP 1222950 A

A laminated board is composed of surface layers made of epoxy resin-glass woven fabric, and an intermediate layer made of epoxy resin and a non-woven fabric contg. a needle-shape inorganic filler in an amt. of 10-250 wt.% based on the resin in the intermediate layer.

Pref., the needle-shape inorganic filler has a needle dia. of 2-20 microns, a needle length of 3-100 microns, and an aspecto ratio of 3-15; the needle-shape inorganic filler is woolastnite.

USE/ADVANTAGE - The laminate has improved mouldability, i.e. the thickness redn. at the edges of the laminate and the void formation are prevented. The heat resistance is high.

O/O

Title Terms: POLYEPOXIDE; RESIN; IMPREGNATE; GLASS; FABRIC; LAMINATE; BOARD  
; INTERMEDIATE; LAYER; CONTAIN; ACICULAR; INORGANIC; FILL; USEFUL; PRINT;  
CIRCUIT; BOARD

Derwent Class: A21; A85; L03; P73

International Patent Class (Additional): B32B-017/04; B32B-027/12

File Segment: CPI; EngPI

?